

725-J53-10封闭漆-灰色  
Tie paint-Grey

产品概述  
Product Description

- 单组分, 连接漆 A one pack tie paint.
- VOC小于450g/L VOC less than 450g/L

用途  
Intended Uses

- 用于连接防锈漆与防污漆的中间漆 Tie coat between anticorrosives and antifoulings.
- 用于新造船, 维修保养及在航保养 For use at Newbuilding, Maintenance and Repair or Maintenance.

产品信息  
Product Information

体积固体份Volume Solids	48%±2%			
光泽度Finish/Sheen	无光Matt			
标准膜厚Typical Film Thickness	50 μm干膜厚 (105 μm湿膜厚) 50 microns dry (105microns wet)			
理论涂布率Theoretical Coverage	9.6m <sup>2</sup> /L(标准膜厚) 9.6m <sup>2</sup> /L at typical film thickness			
混合比Mix ratio	单罐装One pack			
施工方法Method of Application	推荐使用Recommended			
无气喷涂Airless Spray	喷嘴尺寸Tip size range	0.38-0.53mm		
	出口压力Output pressure	≥17MPa		
空气喷涂Air Spray	喷嘴尺寸Tip size range	2.0-3.0mm		
	出口压力Output pressure	≥0.4MPa		
刷涂/辊涂Brush/Roller	适用于小面积施工For small area only			
稀释剂Thinner	不推荐使用, 在特殊情况下, 使用JX-601 (最多不超过体积总量的5%) Not recommended. Use water only in exceptional circumstances (max 5% by volume)			
设备清洗剂Cleaner	JX-601			
熟化时间Induction Period	不适用Not applicable			
干燥参数Drying Information	-5℃	5℃	25℃	35℃
表干Touch Dry	2h	1h	30min	15min
实干Hard Dry	24h	20h	12h	8h
适用期Pot Life	不适用Not applicable			
复涂参数Overcoating Data	底材温度Substrate Temperature			
复涂下列产品时Overcoated by	-5℃	5℃	25℃	35℃
	Min Max	Min Max	Min Max	Min Max
725-J53-10	24h 不限	20h 不限	12h 不限	8h 不限
725-B40-AFB2	24h 不限	20h 不限	12h 不限	8h 不限
725-BE40-16	24h 不限	20h 不限	12h 不限	8h 不限
725-B40-6	24h 不限	20h 不限	12h 不限	8h 不限
贮存Storage	贮存时应保持通风、干燥、防止日光直接照射, 并应隔绝火源, 远离热源, 包装容器必须密闭。贮存温度应大于0℃。在25℃的条件下贮存期为12个月以上 (应以实际检验结果为准)。 Store in cool and dry conditions. Well ventilate. Keep away from hot and fire. Store temperature should be higher than 0℃. Shelf Life: 12 months minimum at 25℃. Subject to re-inspection thereafter.			
包装规格Pack Size	20L容器装24.7kg/18L 24.7kg/18L in 20 L container			
闪点Flash Point	大于28℃ Greater than 28℃			

体系及配套性  
Systems and Compatibility

最适合配套体系请咨询双瑞涂料销售代表。  
Consult your Sunrui Representative for the systems best suited for the surfaces to be protected.

表面处理  
Surface Preparation

采用高压淡水或一般淡水冲洗, 或等效处理, 并按照SSPC-SP1溶剂清理标准除去所有油脂、可溶性污染物及其它污物。所有待涂装表面应保持清洁、干燥。

High pressure fresh water wash or fresh water wash, as appropriate, and remove all oil or grease, soluble contaminants and other foreign matter in accordance with SSPC-SP1 solvent cleaning. All surfaces to be coated should be clean, dry and free from contamination.

725-J53-10应施工在所推荐的底漆上。

725-J53-10 should always be applied over a recommended primer coating system.

在该底漆所规定的复涂间隔内涂装 (参阅底漆的产品说明书)。

Observe the overcoating intervals specified for the primer(consult primer data sheet).

限定  
Limitations

在环境相对湿度85%以下, 待涂表面的温度必须在露点以上至少3℃的条件下施工。

Apply in good weather. Temperature of the surface to be coated must be least 3℃ above the dew point when the humidity is lower than 85%.

干燥时间和复涂间隔可能会由于现场的环境因素而有所改变。

The dry time and overcoating interval may change according to the environment factors.

避免长期吸入溶剂气体或漆雾, 皮肤、眼睛不得接触本品, 施工时注意做好通风及防火措施。

Avoiding absorb the solvent steam and paint steam for long time. Skin and eyes must avoid contacting the paint. Pay attention to ventilate and fireproof when applying.

责任声明  
Duty statement

本产品说明书中提供的信息完全基于我们在实验室和实践中所获得的, 但由于产品的使用通常都是在我们控制范围之外, 我们只给予产品本身质量的保证。我们保留不预先通知而修改说明书的权利。

The data in the sheet base on the information from the laboratory and practice. The application may exceed the control, so we only ensure our product quality. We own the right of the data sheet modification without informing.